

CAVO A 4 ZONE PER SISTEMI A CANALE CALDO

HOT RUNNERS 4 ZONES CABLE





VANTAGGI - ADVANTAGES

- 1. Diametro esterno compatto Compact outer diameter
- 2. Identificazione rapida dei conduttori tutti numerati
 Fast identification of leads through leads
 - marking **Cablaggio rapido**Quick wiring

3.

4. Cavo completo di doppio isolamento No need of outer sheath

CARATTERISTICHE - FEATURES

- Isolamento conduttori in PVC autoestinguente
 Insulation made by flame retardant PVC
- 2. Cavi resistenze numerati
 ID numbered heaters leads
- 3. Cavi termocoppie numerati

 ID numbered thermocouples leads
- 4. Colorazione TC standard IEC (bianco/nero)
 Thermocouples colors according to IEC std.(B/W)
- 5. Guaina esterna in PVC autoestinguente
 Outer insulation made by flame retardant PVC
- 6. Diametro esterno 19 mm
 Outer diameter 19mm

CAVO ARMATO PER HOT RUNNERS 8 / 12 ZONE ARMOURED CABLE FOR HOT RUNNERS 8 / 12 CHANNELS





VANTAGGI - ADVANTAGES

- 1. Diametro esterno compatto Compact outer diameter
- 2. Protezione meccanica integrata nella calza metallica
 - Cut and damage protection made by armoured sheath
- 3. Identificazione rapida dei conduttori tutti numerati
 - Fast identification of leads through leads marking
- 4. Cablaggio rapido Quick wiring
- 5. Cavo completo di doppio isolamento No need of outer sheath

CARATTERISTICHE - FEATURES

- 1. Isolamento conduttori in PVC autoestinguente Insulation made by flame retardant PVC
- 2. Conduttori numerati (1...16 / 1...24)

 ID numbered heaters leads (1...16 / 1...24)
- 3. Sezione conduttori 1,5 mm2
 Leads cross section 1,5 mm2
- 4. Colorazione TC standard IEC (bianco/nero)

 Thermocouples colors according to IEC std.(B/W)
- 5. Isolamento esterno in PVC autoestinguente Outer insulation made by flame retardant PVC
- Calza metallica in acciaio zincato
 Armoured sheath made of galvanized steel

REV.2 del 30/06/14 doc. 7.2.10 pg. 92 / 124