

CAVO TC - TC CABLE TCCA



TEMP. ESERCIZIO (WORKING TEMPERATURE) (TEMP.DE TRAVAILLE)	-25 ÷ +250°C
PICCO (PEAK) (MAXIMALE)	+280°C
TIPO (TYPE)	J, K
PROTEZIONE (PROTECTION) (PROTECTION)	GUAINA METALLICA METAL BRAID GAINE METALLIQUE

MATERIALI	MATERIALS	MATERIAUX
0.22 ÷ 1.0 mm2	0.22 ÷ 1.0 mm2	0.22 ÷ 1.0 mm2
- calza F.V. - calza F.V. - calza in rame stagnato	- F.G. braid - F.G. braid - tinned copper braid	- bas s.verre - bas s.verre - bas en cuivre etainé

SEZIONE SECTION [mm2]	DIA. TOTALE TONDO ROUND OUTER DIA. DIA. EXT. RONDE	DIA. TOTALE OVALE OVAL OUTER DIA. DIA. EXT. OVAL
2 x 0.22	3.0	2.90 x 2.05
2 x 0.35	3.8	3.60 x 2.45
2 x 0.50	4	3.80 x 2.55
2 x 0.80	4.3	4.35 x 3.00
2 x 1.00	4.4	4.40 x 3.10

CAVO TC - TC CABLE TCKK



TEMP. ESERCIZIO (WORKING TEMPERATURE) (TEMP.DE TRAVAILLE)	-100 ÷ +350°C
PICCO (PEAK) (MAXIMALE)	+350°C
TIPO (TYPE)	J, K
PROTEZIONE (PROTECTION) (PROTECTION)	KAPTON KAPTON

MATERIALI	MATERIALS	MATERIAUX
0.22 ÷ 1.0 mm2	0.22 ÷ 1.0 mm2	0.22 ÷ 1.0 mm2
- nastro in KPT - nastro in PTFE - nastro in KPT	- KPT tape - PTFE tape - KPT tape	- ruban en KPT - ruban en PTFE - ruban en KPT

SEZIONE SECTION [mm2]	DIA. TOTALE OVALE OVAL OUTER DIA. DIA. EXT. OVAL
2 x 0.22	1.25 x 2.16
2 x 0.35	1.50 x 2.60
2 x 0.50	1.65 x 2.90
2 x 0.80	1.95 x 3.50
2 x 1.00	2.00 x 3.70

Cavi di estensione per termocoppie di tipo E, S, T, etc. sono disponibili a richiesta.
Extension cables for thermocouples type E, S, T, etc. are available upon request.
Câbles d'extension pour sondes types E, S, T, etc. sont disponibles sur demande.

CARATTERISTICHE TECNICHE - TECHNICAL FEATURES - SPECIFICATIONS ET TOLERANCES

TENSIONE NOMINALE (RATED VOLTAGE) (TENSION NOMINAL)	300/500 V
TENSIONE DI COLLAUDO (TEST VOLTAGE) (TENSION DE TEST)	2000 V
RESISTENZA ALLA FIAMMA (FLAME RESISTANCE) (RESISTANCE A LA FLAMME)	OTTIMA
IMPERMEABILITA' (WATERPROOFING) (IMPERMEABILISATION)	OTTIMA
RAGGIO CURVATURA (BENDING RADIUS) (RAYON DE COURBURE)	5x DIA.
NORME	DIN43714 ANSI MC96.1 IEC 584.3